

## Downlight 725.23 Flush mount NW General Aluminium

REF. 72523033-984



### BASIC INFORMATION

#### DESCRIPTION

The line Downlight 725.23 of the Company Simon, brings together all the conditions needed to achieve a brightness of 100% when switched on. This is due to Simon's extensive experience in the LEDs, which uses all its resources of research to be at the height of the highest quality in the market. This results in the long service life of the luminaire and the resulting saving in maintenance costs due to the fact that the LEDs are not changed often. This also guarantees minimal glare and high visual comfort. Its continuous flicker-free light avoiding visual fatigue and is suitable for places such as hotels, offices, hospitals, etc. This is the luminaire indoor lighting Downlight 725.23 flush-mounted. Colour temperature 3900 K NW Advance. General lighting. The light beam is sent to the bottom with an angle of 40°, which makes the vision of work areas. Category A 30,000 h at 25 ° C. 100-240 V 50 / 60 Hz. ON-OFF switching system with adjustment options of 1-10 V Weight 0.5 kg Material Aluminium. For flush mounting using an accessory. Dimensions 165x51 mm

#### APPLICATION

General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS (LM)

1300 lm

### IP RATING

IP20

### ELECTRICAL CLASS

Type 1

### LUMENS/W

1300 lm/14W

### OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

### INTEGRATED POWER SUPPLY

Yes

### OPTICS

General

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

3900 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

14 W

### CONTROL

On/Off

### COLOR TYPE

NW

### SERVICE LIFE

30.000 h


### CRI

80

### LIGHTING EFFICIENCY (LM/W)

93 lm/W

### CHROMATICS CRI ICONS



## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface

### INSTALLATION TYPE

Flush mount

### MINIMUM INSTALLATION HEIGHT

101

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053116814	3.042
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	80	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.504	195	0.504
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.504	195	KGM