

Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6 UTP graphite Simon 500 Cima

REF. 50002085-038



BASIC INFORMATION

DESCRIPTION

It is plate is designed for voice and data connections of an element and for 1 and 2 RJ45 connectors and is category 6UTP. Includes both the adapter module and RJ45 connectors. It also has dust shutter and supports a cable section of 22-24 AWG. It is one of the many mechanisms of the Simon 500 Cima series. A series focused on create points of work expandable and configurable, integrating the maximum of elements in a minimal space. Also include kits now ready to install. Therefore, any space can be turned into a work point, quick, efficient. Did you know, in addition to the products of the collection Simon 500 Cima are manufactured with the raw materials of the highest quality and halogen-free, avoiding the flame spread in case of fire and smoke? Because the security is not at odds with the design and functionality.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 UTP

KIT AVAILABILITY

Yes

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097991

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.027

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.54

PRODUCT NET WEIGHT

0.027

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

