

LedFlex 810.35 3000 K IP65

REF. 81035100-983



BASIC INFORMATION

APPLICATION

General lighting, Indoor
decorative lighting

PACKAGING CONTENTS

1 unit (5m)

TECHNICAL INFORMATION

IP RATING

IP65

DRIVER INCLUDED

No

LUMENS (LM)

4800 lm

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

LUMENS/W

4800 lm/48W

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

PWM

COLOR TYPE

WW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

100 lm/W

POWER (W)

48 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS
WEIGHT
0.412

PRODUCT NET WEIGHT
0.412

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053202746

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
2

PACKAGING WIDTH
24

PACKAGING LENGTH
25

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
1200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
412.4

PACKAGING NET WEIGHT
0.412

PACKAGING WEIGHT UNIT
GRM