Inspection cover for 2 double elements for installation on pavement or technical floor in graphite Simon Cima

REF. **S200/14**



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With plastic buckets of 2 double elements Simon Cima when installed on pavement floor.

ETIM CLASS

EC001903

TECHNICAL INFORMATION

HEAT RESISTANCE (ºC)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL
7021

RECESS DIMENSION (MM)
170 x 155 mm

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (ºC)
+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

CAN BE INSTALLED IN TRAY
Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436020276

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.785

PRODUCT NET WEIGHT
0.785

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436020276

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
100

PACKAGING WIDTH
190

PACKAGING LENGTH
175

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3325000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.775

PACKAGING NET WEIGHT
0.785

PACKAGING WEIGHT UNIT
KGM