French socket outlet 16A 250V~ with safety device and screw terminal connection white Simon K45

REF. **K02/9**



BASIC INFORMATION

DESCRIPTION

The following French socket outlet is part of the series Simon K45. Capable of supplying power to the electrical equipment and devices of up to 16 empires and 250 volts, it is the perfect socket for the home, office or apartment. This individual socket, made up of two modules, it is easily installed to screw and has a luminous safety device and indicator light. With dimensions of 45 x 45 millimetres and a depth of 39 mm, this socket, traditional white in colour, it is manufactured with metallic material of high quality and halogen-free, it incorporates the latest technology in self-extinguishing halogen-free thermostatic. Thanks to this modern mechanism, this socket outlet reduce the possibility of spread of possible fires and is also designed to reduce the toxicity of smoke product of this. The French socket Simon K45 combines the style classic, thanks to its white colour, with the most modern technology applied at home.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Socket outlet with trim cover

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
1,5 to 2,5 mm

NUMBER OF CONNECTIONS PER TERMINAL
2 connections per terminal (1 input / 1 output)

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

FORMAT
French

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION
No

INSULATION RESISTANCE (V-MΩ)
>5M? At 500 V

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 a 60° C

TYPE OF MECHANISM
Insertion

NUMBER OF MODULES
2 modules

MONOBLOCK
No

NOMINAL VOLTAGE (V~)
250 V~

RAL
9003

NUMBER OF SOCKETS
1

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
12

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE SOCKET
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

NUMBER OF TERMINALS
3 inputs / outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod.|EN IEC 63000:2018|IEC 60884-1 Ed. 3.2|UNE 20315-1-1:2017|UNE 20315-1-2:2017|DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
121251

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.047

PRODUCT NET WEIGHT
0.047

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053122822

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
49

PACKAGING WIDTH
101

PACKAGING LENGTH
245

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1212505

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.5

PACKAGING NET WEIGHT
0.47

PACKAGING WEIGHT UNIT
KGM