

**Complete kit with dual opening cover, metal fin, 6 schuko  
socket outlets and plate for 4 RJ45 connectors black S400  
Indesk Duo**

REF. 47403020-138



## BASIC INFORMATION

### DESCRIPTION

Thanks to this complete kit integrated into the table with a double opening cover, fins, and 6 schuko socket bases and plates for 4 RJ45 in black from the Simon 400 Indesk Duo series, we can have all the necessary connections without the need for long cables on the floor. A piece of cutting-edge design and high-quality materials such as painted steel for the casing or anodized aluminum for the profile, these materials provide the necessary durability to last many years like the first day. Manufactured for 250 volts and a current intensity of 16 amps, it features a Wieland® gst18i 3-pole male aerial connector with a 22 cm patch cord. It has a manual lifting system for easy access to its 6 bases for standard current circuit. Simon is characterized by its safety, an example of which are the covers and fastenings made of halogen-free self-extinguishing thermoplastic, which guarantee the non-propagation of flames and prevent the creation of toxic fumes.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

### RAL

9005

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### CURRENT (A)

16 A

### RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

### IP RATING

IP30

### NUMBER OF RJ45 WINDOWS

4

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### SNAP-FIT TYPE

Keystone I, II and Systimax

### FORMAT

Schuko

### NOMINAL VOLTAGE (V~)

250 V~

### NUMBER OF SOCKETS

6 sockets for standard current circuit

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### VERSION

8 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With metal fin

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45° and 135°

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053208625

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

2.45

### PRODUCT NET WEIGHT

2.45

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053208625

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

370

### PACKAGING WIDTH

135

### PACKAGING LENGTH

200

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

9990000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

2.45

### PACKAGING WEIGHT UNIT

KGM