

## DALI downlight white 735.31 WW General

REF. 73531330-983



### BASIC INFORMATION

#### APPLICATION

Accent lighting, General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### IP RATING

IP44

### DRIVER INCLUDED

Yes

### LUMENS/W

3500 lm/33W

### OPERATING TEMPERATURE RANGE (°C)

Max. temp.: 35°C

### L70 (°C)

50,000 h

### OPTICS

General

### COLOR TEMPERATURE (K)

3000 K

### L90 (°C)

50,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CONTROL

DALI

### COLOR TYPE

WW

### POWER (W)

33 W

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

106,1 lm/W

### SERVICE LIFE

50.000 h

### LUMENS (LM)

3500 lm

## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface-mounted

### INSTALLATION TYPE

Flush-mounted

## REGULATIONS

### WARRANTY

5 years

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053285671

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053285671

PACKAGING VOLUME

9811125

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

135

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

285

PACKAGING NET WEIGHT

1.2

UNITARY PACKAGING GROSS  
WEIGHT

1.5

PACKAGING LENGTH

255

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.2