Floor trunking 2m and 85x18mm with 2 compartments

REF. **TF11172/8**



BASIC INFORMATION

DESCRIPTION

The DCS TF11172/8 floor trunking, with an anodized aluminum cover, is an ideal solution for the distribution of electrical and data cabling indoors. Designed for floor installations, it offers a profile of 85x18 mm, making it perfect for spaces with high connectivity demands such as offices, workplaces, and educational centers. With IK08 mechanical resistance and a maximum load capacity of 45 kg/cm^2, it guarantees durability against impacts, foot traffic, and the occasional passage of vehicles. Its installation system allows for quick fixing with screws and easy maintenance thanks to the removal of the cover with specific tools.

FINISH	MATERIAL	ETIM CLASS
Aluminium	Aluminium	EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION
08

KIT AVAILABILITY
No

RAL
7035

IP RATING
IP4X

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053229088

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
0.75

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436027978

UNITS CONTAINED PACKAGING
8

PACKAGING HEIGHT
90

PACKAGING WIDTH
90

PACKAGING LENGTH
2005

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
16240500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
6

PACKAGING NET WEIGHT
6

PACKAGING WEIGHT UNIT
KGM