

## 2-way switch 16AX 250V~ with 1click® terminal connection system

REF. 7700211-039



### BASIC INFORMATION

#### DESCRIPTION

It is a 2-way switch 16AX 250V~ with 1click ® terminal connection system. This method of installation is much easier and quicker than others, as you do not need to strip cables, so times are reduced considerably. The 2-way switch is included in the Simon 77 series and is suitable for surface or flush mounting. It has been manufactured from metal components with insulation in halogen-free thermoplastic material in compliance with the legislation. Also, it is an article that resists extreme temperatures very well. However, ideally, it should be installed in environments with a temperature range between 5 and 40°C. On the other hand, the collection offers the possibility of implementing signaling function via cradle blinking and rocker with viewer. The Simon 77 series is synonymous with innovative mechanisms, which allow you to clamp without stripping or braiding cables, a revolution of the brand.

#### COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature, Simon 82 and Simon 88 frames

#### PACKAGING CONTENTS

Mechanism and instructions

#### ETIM CLASS

EC001590

#### REMARKS

Possibility of implementing signalling function using cradle blinking and rocker with viewer

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INDICATOR FUNCTION

No

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### CURRENT (A)

16 AX

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### TYPE OF MECHANISM

Pivoting

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW

Simon 27

### INSTALLATION TYPE

Suitable for surface and flush mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008 + EN 60998-2-3:2004

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053256497

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.064

### PRODUCT NET WEIGHT

0.064

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053080092

### UNITS CONTAINED PACKAGING

5

### PACKAGING HEIGHT

82

### PACKAGING WIDTH

83

### PACKAGING LENGTH

223

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

1.518

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.32

### PACKAGING WEIGHT UNIT

KGM