LedFlex 810.34 Fresh Food Bakery IP20

REF. **81034000-920**



BASIC INFORMATION

APPLICATION

General lighting,Indoor decorative lighting

PACKAGING CONTENTS

1 unit (5m)

ETIM CLASS

EC002706

TECHNICAL INFORMATION

IP RATING
IP20

OPERATING TEMPERATURE RANGE (°C)
-20 - 40 °C

COLOR TEMPERATURE (K)
2300 K

CONTROL
PWM

CRI
80

DRIVER INCLUDED
No

L70 (°C)
30,000 h

LIGHT BEAM APERTURE ANGLE (°)
120°

LIGHTING EFFICIENCY (LM/W)
95,4 lm/W

LUMENS (LM)
3625 lm

LUMENS/W
3625 lm/38W

OPTICS
General

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
38 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Hardware

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053202562

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.29

PRODUCT NET WEIGHT
0.171

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053202562

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
2

PACKAGING WIDTH
24

PACKAGING LENGTH
25

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.29

PACKAGING NET WEIGHT
0.171

PACKAGING WEIGHT UNIT
KGM