Downlight 800.21 White 15W 3000K DALI2

REF. **80021330-683**

BASIC INFORMATION

APPLICATION	PACKAGING CONTENTS	ETIM CLASS
General technical lighting	1 Units	EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

CRI
80

LUMENS/W
1100 lm/15W

IP RATING
IP54

ELECTRICAL CLASS
tipo 2

OPTICS
Extensive

OPERATING TEMPERATURE RANGE (ºC)
-15ºC a 35ºC

L70 (ºC)
50.000 h a 25ºC

PHOTOBIOLOGICAL CLASSIFICATION
Categoría exento

POWER SUPPLY (V~)
220/240 V~

LIGHT BEAM APERTURE ANGLE (°)
60º

POWER (W)
15W

COLOR TEMPERATURE (K)
3000K

COLOR TYPE
WW

SERVICE LIFE
50.000 h

CONTROL
DALI2

LIGHTING EFFICIENCY (LM/W)
80 lm/W

COS Φ
0.95

LUMENS (LM)
1100 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT
80

INSTALLATION TYPE
Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

REGULATIONS

WARRANTY
5 years 50.000 h

REGULATIONS
Dir. 2014/35/UE LVD |Dir. 2014/30/UE EMC|Dir. 2009/125/EC ErP (Reg. UE 2019/2020) |Dir. 2009/125/EC ErP (Reg. UE 2019/2015)|Dir. 2011/65/UE RoHS + post. mod|EN 60598-2-2:2012 |EN IEC 55015:2019 + A11:2020|EN 62493:2015 |EN 61547:2009|EN 62717:2017 + A2:2019 |EN IEC 61000-3-2:2019 + A1:2021|EN IEC 63000:2018 |EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053304433

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.43

PRODUCT NET WEIGHT
0.312

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053304433

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
170

PACKAGING LENGTH
175

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3272500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.43

PACKAGING NET WEIGHT
0.312

PACKAGING WEIGHT UNIT
KGM