# LedFlex 810.34 3000 K IP20 HE

REF. **81034000-983**



## BASIC INFORMATION

### APPLICATION

General lighting,Indoor decorative lighting

### PACKAGING CONTENTS

1 unit (5m)

### ETIM CLASS

EC002706

## TECHNICAL INFORMATION

**IP RATING**
IP20

**OPERATING TEMPERATURE RANGE (°C)**
-20 - 40 °C

**COLOR TEMPERATURE (K)**
3000 K

**CONTROL**
PWM

**CRI**
80

**DRIVER INCLUDED**
No

**L70 (°C)**
30,000 h

**LIGHT BEAM APERTURE ANGLE (°)**
120°

**COLOR TYPE**
WW

**LIGHTING EFFICIENCY (LM/W)**
133,3 lm/W

**LUMENS (LM)**
4800 lm

**LUMENS/W**
4800 lm/36W

**OPTICS**
General

**PHOTOBIOLOGICAL CLASSIFICATION**
Exempt category

**POWER (W)**
36 W

## INSTALLATION AND MAINTENANCE

**INSTALLATION TYPE**
Hardware

## REGULATIONS

**WARRANTY**
3 years

# LOGISTICS INFORMATION

UNITARY EAN CODE
8421053202593

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.29

PRODUCT NET WEIGHT
0.171

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053202593

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
2

PACKAGING WIDTH
24

PACKAGING LENGTH
25

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.29

PACKAGING NET WEIGHT
0.171

PACKAGING WEIGHT UNIT
KGM