

PD-24x24 PIR+LUX BT Mesh surface BT-Slave white IP54

REF. 89212636-230



BASIC INFORMATION

DESCRIPTION

Surface presence and brightness detector HF. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 24 x 24 m and the radial detection range is 9 x 9 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The configuration of the detector is done through a Bluetooth application.

Possibility of interconnection between sensors via Bluetooth. The control protocol is Bluetooth slave.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C.

White finish, protection rating IP 54, and dimensions: 123 x 123 x 64 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL

PUSH BUTTON

No

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

Bluetooth Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357880

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.364

PRODUCT NET WEIGHT

0.258

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357880

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.364

PACKAGING NET WEIGHT

0.258

PACKAGING WEIGHT UNIT

KGM