

Adjustable floor box with 4 elements for installation in Simon K45 grey concrete floor

REF. KF470/1



BASIC INFORMATION

DESCRIPTION

The adjustable floor box in the Simon K45 Series is suitable for 4 elements. It is grey in colour and specially designed for recessed installation in concrete floors. However, it can also be installed in a raised floor, expanding its use options. Its dimensions are 171 x 187 millimetres and 76 millimetres deep. Installation is simple and only requires a plastic tray (art. no. 52052102-035) to complete. If it is not installed in the floor finish, the use of a flush-mount trim cover (art. no. 52053102-035) is recommended to completely integrate the product into the space where it is located. The materials used for its manufacture guarantee high quality, as they are based on metal elements with self-extinguishing and halogen-free thermoplastic insulation that ensure the safety of the equipment. These materials are specially designed to avoid the propagation of flames when necessary, and reduce the toxicity of resulting smoke. The adjustable floor box in the Simon 500 Cima Series is suitable for 4 electrical elements. It is grey in colour and specially designed for recessed installation in concrete floors. However, it can also be installed in a raised floor, expanding its use options. Its dimensions are 171 x 187 millimetres and 76 millimetres deep. Installation is simple and only requires a plastic tray (art. no. 52052102-035) to complete. If it is not installed in the floor finish, the use of a flush-mount trim cover (art. no. 52053102-035) is recommended to completely integrate the product into the room where it is located. The materials used for its manufacture guarantee high quality, as they are based on metal elements with self-extinguishing and halogen-free thermoplastic insulation that ensure the safety of the equipment. These materials are specially designed to avoid the propagation of flames when necessary, and reduce the toxicity of resulting smoke.

FINISH

Grey

MATERIAL

Various

COMPATIBILITY

With Simon K45 mechanisms (no adaptor required)

PACKAGING CONTENTS

Floor box, metal partition wall, ground connection cable, screws and installation manual

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product it must be combined with a plastic tray (Art. No. 52052102-035) once configured. Alternatively, it may be combined with flush-mount trim cover (Art. No. 52053102-035) in cases where the same floor finish is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam in the wire outlet

AVAILABLE IN

2, 4, 6, 8 and 12 elements

NUMBER OF CLAMP-HOLDER HOLES

4

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall supplied with the box into the housings fitted for this purpose.

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1400kg

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a +60° C

NUMBER OF MODULES

4 modules

RAL

7011

RECESS DIMENSION (MM)

170 x 155 mm

NUMBER OF SIDE ENTRANCES

8

VERSION

4 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 14 and 54 mm

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using the floor box's fastening claws in the concrete floor tray (supplied with the floor box)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

INSTALLATION DIRECTION

Horizontal

INSTALLATION TYPE

Especially designed to be installed in concrete floors, although it is also suitable for installation in raised floors

REGULATIONS

REGULATIONS

2006/95/CE Directive + UNE-EN 60,670

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053125403

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053125403

PACKAGING VOLUME

3325000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

84

PACKAGING GROSS WEIGHT

1.1

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

181

PACKAGING NET WEIGHT

1.1

UNITARY PACKAGING GROSS
WEIGHT

1.1

PACKAGING LENGTH

212

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.1