

Downlight 725.23 Flush mount NW General 1-10V Aluminium

REF. 72523133-984



BASIC INFORMATION

DESCRIPTION

Downlight 725.23 suitable for flush mounting in ceiling and to provide general lighting, with 1-10 V control and neutral colour temperature (3900 K). The product is in aluminium colour and has a weight of 0.5 kg. This is a downlight very appropriate for uniform lighting of environments and, therefore, manages to create a high visual comfort. For this reason, tends to go to step areas such as corridors, although it is ideal for general lighting for commercial establishments or offices. One of its features is its most praised long service life of up to 30,000 hours. It is enough to give the care essential and will be like the first day. As for its installation, the manufacturer recommends to do it in spaces whose temperature is between -15 and 40°C for better conservation of the article. The most common applications of this downlight are in restaurants and hospitals.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1300 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

1300 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

1-10 V

COLOR TYPE

NW

SERVICE LIFE

30.000 h


CRI

80

LIGHTING EFFICIENCY (LM/W)

93 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053116876	2.888
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	80	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.528	190	0.528
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.528	190	KGM