

Projector 889 20W 3000K

REF. 88931038-883



BASIC INFORMATION

DESCRIPTION

LED outdoor projector for storefront and facade lighting, robust, adjustable, and designed for high performance in commercial applications. Available in different wattages, the outdoor projector 889 allows selecting the appropriate model according to the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 3000K. Power: 20W. Lumens: 2220lm. Efficiency: 111lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 127 mm x 107 mm x 28 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

111 lm/W

LUMENS (LM)

2220 lm

OPTICS

Symmetric

POWER (W)

20 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440506

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.209

PRODUCT NET WEIGHT

0.188

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440506

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

250

PACKAGING WIDTH

190

PACKAGING LENGTH

285

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

13537500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

4.18

PACKAGING NET WEIGHT

0.188

PACKAGING WEIGHT UNIT

KGM