

French double socket outlet 16A 250V~ with safety device and 1Click® terminal connection red Simon 500 Cima

REF. 50000468-037



BASIC INFORMATION

DESCRIPTION

Double French socket outlet with safety device and 1Click ® terminal connection, finished in graphite colour and belonging to the Simon 500 Cima series. It works with a voltage of 250V and current of 16 A and is a socket outlet suitable both for surface and flush mounting. This socket outlet supports a cable section of 1.5 to 2.5 mm and does not require wire stripping. It works in places with temperatures of -25... 60 °C, although it can withstand extreme temperatures. Manufactured with metal components with self-extinguishing, halogen-free thermoplastic insulation, which are materials that guarantees no flame spread (in case of fire) and low toxicity (in the event of smoke). Also, it complies with regulations UNE-EN 60998-2-3 + NF C-61314:2008 + A1:2010. It measures 100 x 50 mm, with a depth of 46 mm, and can be cleaned with just a soft, dry cloth.

FINISH

Red

PACKAGING CONTENTS

Double socket outlet with cover and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

AVAILABLE IN

German and French format

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

FORMAT

French

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

No

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

Yes

LINKABLE

Yes, using accessory 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 60 °C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2

MONOBLOCK

No

RAL

3002

NUMBER OF SOCKETS

2

VERSION

Double

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

REMOVAL OF THE SOCKET

Only with tool

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

1 click connection (1 click®)

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION TYPE

Suitable for surface and flush mounting

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053112755

PACKAGING VOLUME
3.525

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
112

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.111

PACKAGING WIDTH
117

PACKAGING NET WEIGHT
1.11

PRODUCT NET WEIGHT
0.111

PACKAGING LENGTH
269

PACKAGING WEIGHT UNIT
KGM

