

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP aluminium Simon K45

REF. KA95F/8



BASIC INFORMATION

DESCRIPTION

Protect with the highest quality at the best price is the motto of the series Simon K45. In this range, we have the flat plate for voice and data with dust cover for an element and an RJ45 connector of category 5e FTP with insertion tool in aluminium colour. It has dimensions of 45 x 45 x 42 ' 9 mm and a cabling 22-24 AWG. Its installation can be carried out both on a baseboard surface-mounted and in a box flush-mounted into the wall quickly and easily. The metal components with self-extinguishing and halogen-free thermoplastic insulation. of its structure make it very resistant to the negative consequences of knocks, impacts, in addition to being a guarantee for the no flame propagation in case of fire and the low toxicity in case of smoke. This plate, you need to use the 90° positioner (reference K66) to guide the plate into a vertical position.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

RJ45 CONNECTION

With insertion tool

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

Category 5e FTP

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

NUMBER OF MODULES

Four

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.027

PRODUCT NET WEIGHT
0.027

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8426436046146

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.27

PACKAGING WEIGHT UNIT
KGM