

Console for lighting control Touch LightManager Advance graphite Simon Scena

REF. 89000110-038



BASIC INFORMATION

DESCRIPTION

Console for lighting control Touch LightManager Advance, finished in graphite colour and belonging to the series Simon Scena. It works by programming and for use and supports a maximum number of channels of 512. This console, allows you to program and control all the elements of the system and is a version compatible with the Simon Scena app. Programming is done by entirely on the Touch LightManager console without the need for a PC. It offers a control of all types of luminaires (LED, halogens, fluorescents) and communication protocols (DMX, 1-10 V, DALI, PWM). It is fed through a power 100-230 V and features a frequency detailed 50-60 Hz. The functions of the USB port are the following: Update firmware, load and save programs and make customizable logo. Requires flush mounted box 89000990-039 reference and complies with the European standards and regulations UNE -s 50491-3: 2010 + 2004 / 108 / CE + 2006 / 95 / EC. Must be installed vertically, in a place with a temperature range between 0 to 45°C and to clean it, just need to wipe it with a soft cloth slightly moistened in soapy water.

FINISH

Graphite

PACKAGING CONTENTS

Touch LightManager, end-of-line resistor, frame holder and instructions

ETIM CLASS

EC000699

COMPATIBILITY

All types of luminaires and protocols

REMARKS

Requires flush-mount box ref 89000990-039.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

BASIC CHARACTERISTICS

Allows scheduling and control of all system elements; version compatible with the Simon Scena App.

CIRCADIAN CYCLE

Yes

FREQUENCY

50 - 60 Hz

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM NUMBER OF CHANNELS

512

TYPE OF MECHANISM

Touch screen, simple and user-friendly menu browsing

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

OPERATION

Programming and use

POWER CABLE SECTION (MM²)

1.5 mm

POWER SUPPLY (V~)

100/230 V~

STORAGE TEMPERATURE RANGE (°C)

0 - 45 °C

USE

Fast and user-friendly with multiple interfaces, Touch LightManager display, App Simon Scena or optional keypad.

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific

INSTALLATION TYPE

Semi-flush mount.

CABLE CHARACTERISTICS DATA

Multicore AWG 24; 2 shielded twisted pairs with impedance of 120 Ohms

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

UNE-EN 50491-3:2010 + 2004/108/CE + 2006/95/CE

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053125182

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.61

PRODUCT NET WEIGHT

0.61

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053125182

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

77

PACKAGING WIDTH

196

PACKAGING LENGTH

251

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2.947

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.61

PACKAGING WEIGHT UNIT

KGM