

Framework for 8 elements in adjustable floor box graphite Simon 500 Cima

REF. 52051804-038



BASIC INFORMATION

DESCRIPTION

The Simon 500 Cima series offers this kit shallow floor box for 4 elements with 1 double Schuko plug and 2 plates for 1 RJ45 suitable to be installed in raised garden and flooring. Compatible with elements up to 250 Volt voltage and 16 Ampere current, the piece measures 252x180x69 mm and grey finishes in tone. It also allows the insertion by cutting (1 click ®). And thanks to its composition is guarantees that the flame spread if jump is not a fire, in addition to a very low toxicity in case of smoke optionally you can be combined with the flush-mount trim cover if you do not install the same floor covering. From Simon we think always in our customers, so we make sure to offer the highest quality and guarantee at all times. And in our collection Simon 500 Cima is the test of this thanks to the fact that brings together the safest mechanisms on the market.

FINISH

Graphite

COMPATIBILITY

Simon 500 Cima and Simon 27
Play/Simon K45 mechanisms
(using a specific adaptor)

PACKAGING CONTENTS

Framework

MATERIAL

Plastic

ETIM CLASS

EC000007

REMARKS

The adjustable floor boxes include the framework in a white finish. It is recommended to combine this product with the graphite-finish adjustable floor boxes.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

HEAT RESISTANCE (°C)

+125°C (according rule IEC
60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6 and 8 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

8 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V
at 50 Hz for 1 minute

KIT AVAILABILITY

No

RAL

7021

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

VERSION

8 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal, Vertical

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

In concrete floor and raised floor through the adjustable floor boxes

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053254868

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.089

PRODUCT NET WEIGHT

0.089

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093351

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

95

PACKAGING WIDTH

135

PACKAGING LENGTH

230

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2949750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.445

PACKAGING WEIGHT UNIT

KGM

