

Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6A FTP white Simon 500 Cima

REF. 50001089-030



BASIC INFORMATION

DESCRIPTION

This flat base plate of voice and data of 1 element for 2 RJ45 category 6A FTP with dust shutter is white in colour and is included in the Simon 500 Cima series. It measures 50x50 mm and a depth of 44 mm. The plate consists of metal elements with halogen-free material self-extinguishing halogen-free thermoplastic. Its special properties avoid that, in case of fire, there is no flame spread, providing maximum security to the user. The mechanism is with clips that allow its fastening in vertical and horizontal enclosures without you need adapter. To its maintenance, the ideal is to clean the piece with a soft, dry cloth and avoid abrasive products containing chlorine. The Simon 500 Cima series is a collection designed to facilitate the workplace solutions in the spaces thanks to its wide range of mechanisms suitable for all needs.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6A FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097823

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.086

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.72

PRODUCT NET WEIGHT

0.086

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

