

Downlight 725.22 Flush mount WW General IP44 Aluminium

REF. 72522933-983



BASIC INFORMATION

DESCRIPTION

Lighting systems LED Downlights 725 are specially designed to offer a uniform lighting with a high degree of visual comfort. A general indoor lighting of high quality is possible thanks to this luminaire Downlight 725.22 WW advance GENERAL-IP44 suitable for flush in any surface-mounted. Stands out for its warm colour temperature of 3100° K, its general optics that repartite the light in a uniform manner without loss and has a long life 30,000 hours useful. With a consumption of only 24 Watts reaches a light intensity from 2100 lumens, which allows us to a large savings on the electricity consumption. Made to a power supply of 100 - 240 volts with a frequency of 50 / 60 Hertz rate. It has a control system electrical ON-OFF. The dimensions of the piece are 233 x 57 millimetres and it is suitable to be flush mounted in indoor, has a stylish finished in aluminium.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2100 lm

IP RATING

IP44

ELECTRICAL CLASS

Type 1

LUMENS/W

2100 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3100 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

30.000 h


CRI

80

LIGHTING EFFICIENCY (LM/W)

88 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053116784	0.042
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	HLT
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	70	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
1.442	245	1.442
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
1.442	245	KGM