

Voice and data flat plate with dust cover for 1 element for 1 BeldenCDT® RJ45 connector black Simon K45

REF. KA68/14



BASIC INFORMATION

DESCRIPTION

Between connectors and plates for voice and data connections of the series Simon K45 plate we find this voice and data board is fully. The product includes a dust shutter, it is an element for an RJ45 connector BeldenCDT. Its beautiful design commitment to a stylish and versatile finished in black grey colour. This plate is the individual version, with four elements in total. It is available for both one and two connectors in total. If you want to combine the plate in vertical enclosures, it is necessary to purchase the 90 ° positioner Simon reference (: K66), as it is essential to guide the plate into a vertical position. The dimensions are 45 x 45 millimetres, with a depth of 8.5 millimetres. It is manufactured in materials of the highest quality, which advocate by the thermoplastic components, halogen-free that enhance the security in its use. It can be installed in surface-mounted or flush mounted. And does not require any maintenance, since it is enough to clean it with a soft and dry cloth.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

Four

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

BeldenCDT® GigaFlex MDVO.

IP RATING

IP20

RAL

7021

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

BeldenCDT® RJ45 connectors

SNAP-FIT TYPE

BeldenCDT® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.007

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

544320

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436045033

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.145

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

72

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS WEIGHT

0.007

PACKAGING WIDTH

72

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

105