

**Schuko socket outlet 16A 250V~ with safety shutter,
indicator light and screw terminal connection white Simon
K45**

REF. KLS01/9



BASIC INFORMATION

DESCRIPTION

Simon K45 Schuko socket outlet 2 modules and manufactured in white, ideal for positioning in the form of insertion, in any type of room. Screw terminal connection with a voltage of 250V and a current of 16A, it also has a signaling function. It measures 45x45x39 mm and the cable section is from 1.5 to 2.5 mm and wire stripping of 12 mm. The Simon K45 socket is white and has been manufactured with metal components with halogen-free insulation and self-extinguishing thermoplastic. This guarantees no flame spread in case of fire, and low toxicity if there is smoke. The socket is suitable for surface or flush mounting and can be installed in places with temperatures between -5 and 60 ° C.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

socket plug with trim cover and indicator light

ETIM CLASS

EC000125

REMARKS

Possibility to order replacement for pin, in the event of breakage or loss, through Art.No. AC33/6

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

NUMBER OF MODULES

2 modules

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal (1 input / 1 output)

CURRENT (A)

16 A

MONOBLOCK

No

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

FORMAT

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

9003

NUMBER OF SOCKETS

1

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

REMOVAL OF THE SOCKET

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION TYPE

Suitable for surface and flush mounting

NUMBER OF TERMINALS

3 inputs / outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.052

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

1212505

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053123454

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

121251

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.52

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

49

PACKAGING NET WEIGHT

0.52

UNITARY PACKAGING GROSS

WEIGHT

0.052

PACKAGING WIDTH

101

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

245