


Flush-mount wall box for 3 double elements Simon 500 Cima

REF. 51020103-039



BASIC INFORMATION

MATERIAL

Plastic

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms using a specific adaptor

PACKAGING CONTENTS

Flush-mount wall box, protective cover for box and film for covering the pre-punched items on the box

ETIM CLASS

EC002601

REMARKS

The flush-mount box can be used as a template during installation thanks to the guides for marking the perimeter of the box

TECHNICAL INFORMATION

AVAILABLE MARKET CE

AVAILABLE IN

1, 2, 3, 4 and 6 double elements

NUMBER OF CLAMP-HOLDER HOLES

10

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housing fitted into the box for this purpose.

NUMBER OF ENCLOSURES FOR GROUND CONNECTION

2

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

IK CLASSIFICATION

07

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

6

NUMBER OF PRE-PUNCHED HOLES 30 X 70 MM

2

RECESS DIMENSION (MM)

199 x 141 mm

NUMBER OF SIDE ENTRANCES

2

VERSION

3 double elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 4 and 30 mm

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using the claws included in the enclosure, in combination with aggregates, binders, additives, etc.

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for flush mounting on the wall

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053090770

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.3

PRODUCT NET WEIGHT

0.3

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053090770

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

52

PACKAGING WIDTH

165

PACKAGING LENGTH

225

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1.93

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT


0.32

PACKAGING NET WEIGHT


0.3

PACKAGING WEIGHT UNIT

KGM



• Grosor pared de 4 a 30mm



Tabique obra
Tabique hueco

