# Complete table-top kit with 3 German socket outlets and plate for 2 RJ45 connectors aluminium Simon 400

REF. **42403020-133**



## BASIC INFORMATION

### DESCRIPTION

For those who are looking for a electrical connection efficient and without the need to search for connections in the wall, Simon presents this kit of desk top. Product of great quality made of metal with an aluminium finish, the trim cover is made of painted steel while the profile is aluminium adonizado, the covers and fastenings are designed to offer the maximum security as they are manufactured in self-extinguishing thermoplastic which prevents the expansion of the flame in case of fire. This piece belongs to the series Simon 400 and has 3 socket-outlets plug and plate for 2 RJ45 connectors, with dimensions of 2015 x 120 x 80 millimetres we find the version of 4 elements, suitable for incorrect voltages of 250 volts and current of 16 amps. A product that has a manual elevation system, thanks to which we will be able to access to it in a comfortable and simple way.

### FINISH

Aluminium

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9006

### NUMBER OF RJ45 WINDOWS
2

### SNAP-FIT RJ45 PLATES
Keystone® I, II and Systimax®

### SNAP-FIT TYPE
Keystone® I, II and Systimax®

### NUMBER OF SOCKETS
3 sockets for standard current circuit

### VERSION
4 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

### INSTALLATION TYPE
Suitable for fixing to furniture.

### SECURING POSSIBILITIES
Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053195697

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING GROSS WEIGHT
0.8

### PRODUCT NET WEIGHT
0.8

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053195697

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
90

### PACKAGING WIDTH
116

### PACKAGING LENGTH
298

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
3111120

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0

### PACKAGING NET WEIGHT
0.8

### PACKAGING WEIGHT UNIT
KGM