

IP66 watertight raised floor box kit with 1 schuko socket outlet + 1 narrow blind cover and sheath

REF. KGH110RF/72



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of watertight floor boxes for indoor and outdoor environments. This is a kit that includes the manual closing mechanism frame with 1 schuko and 1 K45 blank plate of 22.5x45mm, to be integrated into the included housing for installation in raised flooring with cutting dimensions of 125 x 125 mm. The product design, combined with its mechanism frame made of stainless steel, ensures a robust, solid, and secure installation as it can withstand a water jet of 1 kg/cm² from any direction, achieving a protection rating of IP66 when the lid is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal bending radius for wiring in high-category voice and data connections. Our accessory for plug connection with the lid closed is available, allowing us to keep our connections active with an IP54 (see reference KFA1001), the possibility to level our box in case of irregular flooring (see reference KFA1003), or the ability to concatenate more than one box (see reference KFA1002).

FINISH

Steel

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

TECHNICAL INFORMATION

FORMAT

Schuko

IP RATING

IP66

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg -
Open box

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

RECESS DIMENSION (MM)

125x125

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard
IEC 60670)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60670-23:2008 | EN IEC 63000:2018 | IEC
60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053355459

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.933

PRODUCT NET WEIGHT

0.852

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053355459

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

1050

PACKAGING WIDTH

1600

PACKAGING LENGTH

1700

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2856000000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.933

PACKAGING NET WEIGHT

0.852

PACKAGING WEIGHT UNIT

KGM