

Italian bipasso socket outlet 10/ 16A with screw terminal connection 1 element graphite K45

REF. K06/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation on wall, floor, ceiling, and furniture and Simon 500 Cima enclosures (requires combination with K45 to 500 Cima adapter ref. 50012088-030).

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Bipasso

IP RATING

IP20

RAL

7021

CURRENT (A)

10 / 16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053314104

PACKAGING VOLUME
1470000

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
20

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
245

PACKAGING GROSS WEIGHT
0.599

UNITARY PACKAGING GROSS
WEIGHT
0.026

PACKAGING WIDTH
50

PACKAGING NET WEIGHT
0.52

PRODUCT NET WEIGHT
0.026

PACKAGING LENGTH
120

PACKAGING WEIGHT UNIT
KGM

