

Rocker for single-pole switching mechanisms for 1 element aluminium Simon K45

REF. K109/8



BASIC INFORMATION

DESCRIPTION

Rocker for single-pole switching mechanisms of 1 element finished in aluminium and belonging to the Simon 27 series, a collection designed to facilitate the workplace solutions in the work stations. This product is suitable for surface or flush mounting installation. It is manufactured in halogen-free thermoplastic material, which offers maximum protection in case of fire, as prevents the flame spread, and also considerably reduces the toxicity if any smoke. The rocker complies with the current regulation and measures 45 x 22.5 x 10 mm. To clean it, wipe gently with a soft, dry cloth. Avoid abrasive cleaners containing chlorine. Remember, it is not possible to combine 2 control mechanisms with a narrow rocker in a Simon 500 Cima to Simon K45 adaptor plate.

FINISH

Aluminium

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Rocker and installation manual

ETIM CLASS

EC000011

REMARKS

It is not possible to combine 2 narrow button control mechanisms on a Simon 500 Cima-Simon K45 adapter plate

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Quarter and half module versions

KIT AVAILABILITY

No

NUMBER OF MODULES

Four

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

PRODUCT NET WEIGHT
0.008

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING VOLUME
544320

UNITARY PACKAGING LENGTH
0

PACKAGING EAN
8426436047020

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
544320

UNITS CONTAINED PACKAGING
5

PACKAGING GROSS WEIGHT
0.04

UNITARY PACKAGING VOLUME
UNIT
MMQ

PACKAGING HEIGHT
72

PACKAGING NET WEIGHT
0.04

UNITARY PACKAGING GROSS
WEIGHT
0.008

PACKAGING WIDTH
72

PACKAGING WEIGHT UNIT
KGM

PACKAGING LENGTH
105