

Push-button switch with bell symbol 10A 250V~, built-in light and fast terminal connection system white Simon 31

REF. 31660-30



BASIC INFORMATION

DESCRIPTION

White push-button switch from the Simon 31 series, with bell symbol, built in LED system and quick terminal connection. It works with a voltage of 250V and current of 10A and has has a rocker operation. This push-button switch can be combined with article 31802-31 if you need to replace the indicator light. Has 1 element and 2 modules and supports a cable section of 1.5 to 2.5 mm, with a wire stripping of 11 mm and can be installed perfectly in places with a temperature of between 5 and 40°C, although it is capable of withstanding extreme temperatures of -25 to 50°C, approximately. It complies with regulations UNE-EN 60669-1:2002 + A1:2003 + A2:2009 and is manufactured with metal components with halogen-free thermoplastic insulation and thermoset trim. It measures 64x65 mm and is cleaned with a soft cloth slightly moistened in soapy water, without the use of abrasive cloths or cleaners with chlorine.

FINISH

White

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

CONSUMPTION INDICATOR (mA)

1 mA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053006467

PACKAGING VOLUME
3026595

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
83

PACKAGING GROSS WEIGHT
0.915

UNITARY PACKAGING GROSS
WEIGHT
0.092

PACKAGING WIDTH
165

PACKAGING NET WEIGHT
0.92

PRODUCT NET WEIGHT
0.092

PACKAGING LENGTH
221

PACKAGING WEIGHT UNIT
KGM