Bottom closure for Teleblock telescopic profiles with manual elevation Simon K45

REF. **KTLA6**



BASIC INFORMATION

DESCRIPTION

It is a bottom closure designed for Teleblock telescopic profiles with manual elevation included in the series Simon K45. This collection was created with the aim of facilitating the workplace solutions in the work stations. To do this, it has a series of solutions to be installed easily and quickly, raising the connections to the highest level. These solutions of the series Simon K45 stand out, in addition, due to be perfectly into the furniture. This product measures 102 x 59 x 23 mm and is finished in black. Also, is made of thermoplastic material and self-extinguishing halogen-free, designed to guarantee no flame spread in case of fire of a fire. The same way, ensuring the low toxicity in case of smoke. For optimum preservation of this article, it is recommended to install it in environments with a temperature range between -5 and 60 ° C

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Bottom closure for telescopic profiles with manual elevation.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MOhm at 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

LINKABLE
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

RAL
7021

INSTALLATION AND MAINTENANCE

CABLING ACCESS
Through the space enabled in the lower part of the profile.

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

TYPE OF FASTENING
Using the thread on the screws that ensures closure on the Simon K45 Teleblock telescopic profile. Note: this article is a replacement part and is supplied with the Simon K45 Teleblock telescopic profile.

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436056558

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.055

PRODUCT NET WEIGHT
0.055

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436056558

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
59

PACKAGING WIDTH
66

PACKAGING LENGTH
105

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.3

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.045

PACKAGING NET WEIGHT
0.055

PACKAGING WEIGHT UNIT
KGM