

Metal mini-tower 5 heights and 1 side for 10 elements stainless steel Simon K45

REF. KT0100/8



BASIC INFORMATION

DESCRIPTION

Metal mini-tower 5 heights and one side. This torre is for 10 elements and its finish is committed to a stylish stainless steel. It belongs to the series Simon K45. The dimensions of the mini-tower Simon are 361,5 x 221 millimetres, with a depth of 68 millimetres. The products fixed to the floor Simon advocate for the maximum quality of its materials, and also for providing a great functionality. This mini-tower is available in 4 or 5 heights and have five double modules. The centre frames include linkable parts that form blocks. In this way it is possible to separate the electrical part from the voice and data. This is much easier to optimize the maintenance of the product. Thanks to its materials of maximum security, the torre can withstand very variable temperatures, which reaches up to the 12° degrees centigrade maximum. The product is suitable to install it on any floor type, whether raised or concrete.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC001941

MATERIAL

Stainless steel

PACKAGING CONTENTS

Metal mini-tower, protective foam, metal separator, ground connection cable, screws and installation manual

REMARKS

The centre frames include linkable parts that make blocks, allowing separate the electrical part of the part of voice and data for ease of maintenance

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam between the fastening base and mini-tower structure.

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

EARTHING RESISTANCE

< 0.05 Ω

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Guaranteed through the installation of the metal separator in the housing fitted into the mini-tower for this purpose.

HEAT RESISTANCE (°C)

+850°C (according rule IEC 60695-10-2)

IK CLASSIFICATION

08

INSULATION RESISTANCE (V-MΩ)

>5 MΩ to 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 120° C

NUMBER OF MODULES

5 double modules

VERSION

1-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using supplied screws

REMOVAL OF THE FRAME

Only with tool

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053092668

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.42

PRODUCT NET WEIGHT

2.42

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053092668

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

67

PACKAGING WIDTH

168

PACKAGING LENGTH

398

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4.48

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.42

PACKAGING WEIGHT UNIT

KGM