

**Single-pole switch 10AX 250V~ with fast terminal connection system ivory Simon 27 Play**

REF. 27101-62



## BASIC INFORMATION

### DESCRIPTION

Design and innovation tandem form the perfect in the single-pole switch of the Simon 27 Play collection, with finishes in stylish ivory colour, this rocker switch is composed of 2 modules and has a size of 45 x 45 mm, it facilitates the integration of the set in all types of spaces and decorative styles. The convenience of a quick terminal connection, adds an installation suitable for recessed or surface-mounted, compatible with power supply of 250 Volts and 10 AX current with a cross-cable section cross-section of 1.5 to 2.5 mm and stripping of 11 mm Made of halogen-free thermoplastic and a thermoset trim, it protects the room is a possible fire, to prevent the flame spread and reduce the level of toxicity by smoke. Simon 27 Play maximize the versatility of single-pole switch to replace the finish of the supplied rocker for one of the 7 additional. Innovation, functionality and versatility in the entire range of switches Simon 27 Play.

### FINISH

Ivory

### COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

### PACKAGING CONTENTS

Mechanism with rocker

### ETIM CLASS

EC001590

### REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 7 additional finishes available.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CURRENT (A)

10 AX

### OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### IP RATING

IP21

### STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### VERSION

Single

### INDICATOR FUNCTION

No

### TYPE OF MECHANISM

Pivoting

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

11

### CLAW

Simon 27

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and  
Centralisations

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

Suitable for surface and flush  
mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053251423

UNITARY PACKAGING HEIGHT

45.5

UNITARY PACKAGING WIDTH

38.1

UNITARY PACKAGING LENGTH

45.5

UNITARY PACKAGING  
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.079

UNITARY PACKAGING VOLUME  
UNIT

DMQ

UNITARY PACKAGING GROSS  
WEIGHT

0.032

PRODUCT NET WEIGHT

0.013

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING EAN

8421053035474

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

53

PACKAGING WIDTH

160

PACKAGING LENGTH

220

PACKAGING MEASUREMENT  
UNIT

MMT

PACKAGING VOLUME

1.866

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.315

PACKAGING NET WEIGHT

0.13

PACKAGING WEIGHT UNIT

KGM

# MECANISMOS SIMON 27, 28 Y 44

## Mecanismos básicos / Basic switches



Interruptor unipolar / Single-pole switch  
XX00101-XX



Pulsador / Push button switch  
XX00150-XX



Interruptor bipolar / Double pole switch  
XX00133-XX



Conmutador / 2-way switch  
XX00201-XX



Conmutador cruce / Intermediate switch  
XX00251-XX

## Mecanismos con piloto / Pilot switches



Interruptor unipolar / Single-pole switch  
XX00102-XX



Interruptor bipolar / Double pole switch  
XX00134-XX



Conmutador / 2-way switch  
XX00202-XX



Interrupor unipolar / Single-pole switch  
XX00104-XX



Pulsador / Push button switch  
XX00160-XX



Conmutador / 2-way switch  
XX2700204-XX



Conmutador cruce / Intermediate switch  
XX2700254-XX