

Bipolar thermal-magnetic 16A with double element trim plate and 42 mm height aluminum Simon Cima

REF. S195AS/8



BASIC INFORMATION

FINISH

Aluminium

COMPATIBILITY

With Simon Cima Pro surface-mounted and flush-mounted wall boxes, Cima Classic flush-mounted wall boxes with a 33mm housing, adjustable and reduced-depth floor boxes, and PVC cable guide trunking.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)

6000 A

KIT AVAILABILITY

No

POWER SUPPLY (V~)

400 V~

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TRIP CURVE

C Curve

IP RATING

IP20

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REMOVAL OF THE MCB

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050150

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

753878

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.282

PRODUCT NET WEIGHT

0.282

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

118

PACKAGING WIDTH

121

PACKAGING LENGTH

264

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3769392

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.41

PACKAGING NET WEIGHT

1.41

PACKAGING WEIGHT UNIT

KGM