Industrial luminaire 816.44 4000K GN

REF. **81644038-784**



BASIC INFORMATION

APPLICATION

Accent lighting,General lighting

ETIM CLASS

EC001716

TECHNICAL INFORMATION

IK CLASSIFICATION
08

IP RATING
IP65

COLOR TEMPERATURE (K)
4000 K

CONTROL
DALI

CRI
80

L70 (°C)
50.000 h at 25°C

LIGHT BEAM APERTURE ANGLE (°)
90°

LIGHTING EFFICIENCY (LM/W)
128 lm/W

LUMENS (LM)
30900 lm

LUMENS/W
30900 lm / 240W

OPTICS
General

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
240 W

SERVICE LIFE
50.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Discontinued

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053229361

UNITARY PACKAGING HEIGHT
200

UNITARY PACKAGING WIDTH
485

UNITARY PACKAGING LENGTH
485

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
47045000

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
8

PRODUCT NET WEIGHT
6.6

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053229361

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
200

PACKAGING WIDTH
485

PACKAGING LENGTH
485

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
47045000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
8

PACKAGING NET WEIGHT
6.6

PACKAGING WEIGHT UNIT
KGM