

PD-20x3 Hallway HF+LUX surface On/Off white IP20

REF. 89215135-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for surface HF. The recommended installation height is 2.8 m, with a maximum height of 3 m. It has a detection angle of 360 ° and an opening angle of 140 °. The tangential detection range is 20 x 3 m and the radial detection range is 20 x 3 m.

The brightness regulation range is 10 - 1000 lux and the timing range is 30 s - 30 min. The configuration of the detector is done via potentiometers and remote control.

It features TEACH operating mode. Possibility of interconnection between master/master and master/slave sensors up to 10 detectors. The control output is On/Off and the maximum switchable power is 1500 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -25 - 55 °C. White finish, protection rating IP 20 and dimensions: 120 x 120 x 70 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1500

RAL

9010

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357682

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.479

PRODUCT NET WEIGHT

0.262

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357682

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

100

PACKAGING LENGTH

145

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.479

PACKAGING NET WEIGHT

0.262

PACKAGING WEIGHT UNIT

KGM