MCB 10A for 1 element with trim plate white Simon K45

REF. **K106A/9**



BASIC INFORMATION

DESCRIPTION

The Miniature circuit breaker for one element with trim plate in white colour of the series Simon K45 is one of the mechanisms and base plates for circuit protection most in demand today, with an intensity of 10 A, this piece has been manufactured with metal components with self-extinguishing and halogen-free thermoplastic insulation.; guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation. Its installation can be carried out in a simple way in a few minutes in any enclosure wall-mounted, floor, ceiling or furniture of the range K45 and Simon 500 Cima through the adaptor 50012088-030. It has dimensions of 45x45x47 mm, supports a section of wire up to 25 mm and it has a stripped wire 10 mm, all this at a price for all types of pockets with the best quality.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture.

PACKAGING CONTENTS

10 A two-pole circuit breaker and Simon K45 format trim plate

ETIM CLASS

EC000042

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
Up to 25 mm

BREAKING CAPACITY (A)
3000 A

NUMBER OF CONNECTIONS PER TERMINAL
1 input per terminal connector

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

CURRENT (A)
10 A

IP RATING
IP44

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

TYPE OF MECHANISM
Two-pole

NUMBER OF MODULES
Half

POWER SUPPLY (V~)
230 V~

RAL
9003

TRIP CURVE
C Curve

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for installation in any wall, floor, ceiling or furniture enclosure of the Simon 500 Cima and K45 range using the adaptor 50012088-030

REMOVAL OF THE MCB
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

NUMBER OF TERMINALS
4 (1 terminal connector per pole)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60898-1:2003 + EN 60898-1:2003 A1:2004 + EN 60898-1:2003 A11:2005 + EN 60898-1:2003 A12:2008 + EN 60898-1:2003 A13:2012

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436040151

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.08

PRODUCT NET WEIGHT
0.08

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436040151

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
50

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
288800

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.706

PACKAGING NET WEIGHT
0.08

PACKAGING WEIGHT UNIT
KGM