

# Linear Light module 860 Low UGR 1600 4000 K

REF. 86002300-584



## BASIC INFORMATION

### APPLICATION

Residential

### PACKAGING CONTENTS

1 unit

### ETIM CLASS

EC000996

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### VOLTAGE (V~)

220/240 V~

### LUMENS (LM)

2707 lm

### IP RATING

IP20

### COLOR TEMPERATURE (K)

4000K

### LUMENS/W

139 lm/W

### OPERATING TEMPERATURE RANGE (°C)

Ta Max 35°C

### CONTROL

DALI

### MACADAM STEPS

< 3 Step MacAdam

### POWER SUPPLY (V~)

220/240 V~

### CRI

80

### POWER (W)

19.5 W

## REGULATIONS

### EAC MARKED

No

### ECORRAE MARKED

No

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053298961

### UNITARY PACKAGING HEIGHT

60

### UNITARY PACKAGING WIDTH

60

### UNITARY PACKAGING LENGTH

1615

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

5814000

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

1.6

### PRODUCT NET WEIGHT

1.27

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053298961

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

60

### PACKAGING WIDTH

60

### PACKAGING LENGTH

1615

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

5814000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

1.6

### PACKAGING NET WEIGHT

1.27

### PACKAGING WEIGHT UNIT

KGM