

PD-40 Large Areas PIR+LUX surface KNX round black IP54

REF. 89218739-138



BASIC INFORMATION

DESCRIPTION

Surface PIR presence and light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 40 m and the radial detection range is 8 m. The light regulation range is 2 - 1000 lux and the timing range is 1 min - 255 min. The detector configuration is performed via potentiometers and KNX. It features a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 12.5 mA. The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. Black finish, IP 54 protection degree, and dimensions: Ø 126 x 65 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP54

RAL

9005

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343081

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.253

PRODUCT NET WEIGHT

0.164

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053343081

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1785600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.253

PACKAGING NET WEIGHT

0.164

PACKAGING WEIGHT UNIT

KGM