Projector 889 150W 3000K

REF. **88934038-883**



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for shop window and facade lighting, robust, adjustable and designed for high performance in commercial applications. Available in different power ratings, the 889 outdoor projector allows selecting the appropriate model according to the mounting height, the surface to be illuminated and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 3000K. Power: 150W. Lumens: 13500lm. Efficiency: 90lm/w. IP protection grade: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 331 mm x 278 mm x 47 mm.

APPLICATION

Wall lighting,Industrial lighting,Commercial areas

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
05

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+50

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
90 lm/W

LUMENS (LM)
13500 lm

OPTICS
Symmetric

POWER (W)
150 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440322

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.607

PRODUCT NET WEIGHT
1.53

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440322

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
300

PACKAGING WIDTH
230

PACKAGING LENGTH
355

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
24495000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
6.428

PACKAGING NET WEIGHT
1.53

PACKAGING WEIGHT UNIT
KGM