

Modular Luminaire 720 Advance M4 60x60 NW

REF. 72060040-884



BASIC INFORMATION

DESCRIPTION

High efficiency and maximum quality and innovation with the luminaire 720 modular Advance M4 of the collection Simon. With translucent optics and colour white neutral, this luminaire is composed of multiple LEDs to ensure a greater efficiency and sustainability with the environment. With luminous light flux 4100 lumens for NW, and total luminaire consumption of 34 W, includes system of constant light control (CLC) to maximize the natural light of the space in perfect harmony with light artificial of the luminaire. Compatible with power supplies 100-240 V / 50-60 Hz, has a service life of 40,000 hours at 25 ° C With a size of 595 x 595 x 60 mm and finishes in white, it is designed for installation in false ceiling, visible hardware and, in addition to its format is square, guaranteeing the integration of the set in the space, providing a stylish and minimalist style.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

146 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

4100 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

4100 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053124697

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.58

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053124697

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

600

PACKAGING LENGTH

600

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

5.58

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM