

**Two-pole socket outlet 16A 250V~ for half element with
safety device and screw terminal connection white Simon
27 Play**

REF. 27431-64



BASIC INFORMATION

DESCRIPTION

It is a two-pole socket-outlet 16A 250V~ of half an element that includes a device of security. With a white finish, the mechanism offers a system of screw-terminal connection. Remember that a proper terminal connection guarantees the correct functioning of the device is also suitable for replacement or export. This two-pole socket-outlet it is composed of metal parts with halogen-free thermoplastic halogen-free and trim made of thermostable plastic. The quality of these materials allows the mechanism to be installed in any environment, as it is highly resistant to extreme temperatures, measures 22.5x45 mm and does not contain any engraving. It is part of the Simon 27 Play series, a collection that allows you to take the initiative in redecorating spaces. Its mechanisms are equipped with innovative electronic functions adapted to current needs.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

Suitable for replacement or export.

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Two-pole

TYPE OF MECHANISM

Insertion

VERSION

Single

INDICATOR FUNCTION

No

MONOBLOCK

No

VOLTAGE (V~)

250 V~

CURRENT (A)

10 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252062

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.033

PRODUCT NET WEIGHT

0.033

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053038086

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

52

PACKAGING WIDTH

105

PACKAGING LENGTH

220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1201200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.665

PACKAGING NET WEIGHT

0.66

PACKAGING WEIGHT UNIT

KGM