

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP black Simon K45

REF. KA95F/14



BASIC INFORMATION

DESCRIPTION

Always with the highest quality and excellent design, Simon offers us a new way of connection thanks to the series Simon K45. In it we will find from systems modular columns, surface-mount boxes or floor, always with the best materials and finishes. As this plate for connection of voice and data with flat form, an element and with RJ45 connector of category 5e, supports 22-24 AWG of wire in colour and has a white finish, it can be installed for surface-mounted or recess and is very easy to clean. If necessary, in addition, this plate can be combined with vertical enclosures. To do this, it is necessary to use the positioner Simon K66 to be able to set the plate into a vertical position. Without a doubt, the series Simon K45 is your ally perfect to solve all those problems of connection that may appear in your workplace.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Four

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

IP RATING

IP20

RAL

7021

RJ45 CONNECTION

With insertion tool

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436067837

PRODUCT NET WEIGHT

0.024

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436046122

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

2.5

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.24

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.024

PACKAGING LENGTH

140