

Satellite socket single F type female with trim plate white Simon K45

REF. K102C/9



BASIC INFORMATION

DESCRIPTION

Simon is without doubt synonymous with quality, innovation, appearance and security. For over 100 years have achieved provide us the best products for inside and outside of the home and be able to get the most complete work stations and business environments, always, without losing a pinch in elegance, thanks to its modern and avant-garde designs. Within the workplace solutions for the home, we find the collection K45, focused on improving any type of connection where it is needed. This is why this range is designed for offices, meeting rooms, hospitals or any public space. In this series, K45, we find this single satellite socket, female, with trim. Of a module and half element, this single F type have a finish is white in colour and can be applied to both to be recessed and surface-mounted. Supports a maximum length of 90 metres wire RG-6 and dimensions 22.5 x 45 mm

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Simple F type female satellite socket

ETIM CLASS

EC000439

REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

CABLE SECTION ADMITTED (MM)

From 6 to 8 mm

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

CONNECTOR TYPE

SAT

NUMBER OF WIRES

1

NUMBER OF CONTACTS

1

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1/2 element

RAL

9003

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 50083-2:2012 + A1:2015 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.014

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046528

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

91140

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.14

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS
WEIGHT

0.014

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140