Complete flush-mounted in the desk kit with cover, metal fin, 2 German socket outlets, 2 UPS socket outlets and plate for 4 RJ45 connectors aluminium Simon 400

REF. **45602240-133**



BASIC INFORMATION

FINISH
Aluminium

MATERIAL
Metal

COMPATIBILITY
Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS
Pre-wired profile, enclosure, fastening claws and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with metal fin

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9006

RECESS DIMENSION (MM)
318 x 175 mm (± 2mm)

NUMBER OF RJ45 WINDOWS
4

SNAP-FIT RJ45 PLATES
Keystone I, II and Systimax

SNAP-FIT TYPE
Keystone I, II and Systimax

NUMBER OF SOCKETS
2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

NUMBER OF UPS SOCKET OUTLETS
2

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
With metal fin

CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for recessed mount in furniture.

OPENING ORIENTATION
At 45º

SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053208465

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.25

PRODUCT NET WEIGHT
2.25

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053208465

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
330

PACKAGING WIDTH
195

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5791500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.25

PACKAGING WEIGHT UNIT
KGM