

Waterproof linear luminaire BT Mesh 42W 4000K with detector 10m HF+LUX IP65

REF. 89392600-424



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and Bluetooth connectivity. The power is 42.4 W, the luminous flux is 5940 lm, and the color temperature is 4000 K. The maximum installation height is 4m, and the installation is surface-mounted. The detection range is 10m, and the detection angle is 360°. The brightness regulation range is 2 - 2000 lux, and the timing range is 5 s - 60 min. The configuration of the luminaire is done via a Bluetooth application. Possibility of interconnection between luminaires through Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection rating IP 65 and IK 7, with dimensions: 1500 x 87 x 58 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP65

IK CLASSIFICATION

07

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343272

UNITARY PACKAGING GROSS WEIGHT

2.2

PACKAGING LENGTH

1690

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.77

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

14872000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053343272

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.2

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING NET WEIGHT

1.77

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

110

PACKAGING WEIGHT UNIT

KGM