Extension 1.5 metres for aluminium column with 2 sides oval Simon K45

REF. **ALK72P15/8**



BASIC INFORMATION

DESCRIPTION

Among Simon's fixed to the floor products, is this extension of 1.5 metres aluminium oval column with two sides. It is part of the series Simon K45. It can withstand extreme temperatures, ranging from -25 degrees centigrade up to the + 120 degrees centigrade maximum. With measures of 1500 x 80 millimetres and a depth of 110 millimetres in total, this extension for column a stylish metallic finish. To accomplish this, anodised aluminium was used in its manufacture. To ensure the robustness of the set, it is only possible to combine one extension per column. For its correct maintenance, simply use a very soft cloth, cotton, and completely dry cloth for cleaning. Always avoid the use of aggressive chemical products, with the manufacturing materials of this extension. Simon guarantees the security of all its products fixed to the floor, as well as the best functionality of the same.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

AVAILABLE IN
2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+120º C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (ºC)
+650ºC (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-25 a 120º C

VERSION
2-sided (Oval)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050563

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
31834880

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
4

PRODUCT NET WEIGHT
4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436050563

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
88

PACKAGING WIDTH
119

PACKAGING LENGTH
3040

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
31834880

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
4

PACKAGING WEIGHT UNIT
KGM