

Single-pole switch 10AX 250V~ with built-in light and fast terminal connection system champagne Simon 31

REF. 31104-34



BASIC INFORMATION

DESCRIPTION

With a design of simple lines and finishes in a stylish champagne colour, the single-pole switch of the collection Simon 31, it adapts to all kinds of environments, thanks to its decorative timeless design of notes minimalist, with indicator light, built-in and quick terminal connection, innovation and functionality to be the perfect balance in this product. With a size of 64 x 65 mm, it consists of two modules with capacity for 1 element and supports a wire cross section of 1.5 to 2.5 mm and stripping of 11mm. It is also compatible with a power of 250 Volt voltage and 10 AX intensity, and the signal function has a consumption of 1 mA. It is made of metal components with halogen-free insulation and thermoplastic trim, metallised, protecting the room in case of fire, and can reach maximum temperatures of -25 to 50 °C. If you need to replace the indicator light, Simon 28 recommends combining it with the product reference 31802-31.

FINISH

Champagne

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC001590

REMARKS

Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

CONSUMPTION INDICATOR (mA)

1 mA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF POSSIBLE ELEMENTS

1 element

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INDICATOR FUNCTION

Yes

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush
mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.091

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053008638

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

3026595

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.91

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

83

PACKAGING NET WEIGHT

0.91

UNITARY PACKAGING GROSS

WEIGHT

0.091

PACKAGING WIDTH

165

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221

MECANISMOS SIMON 31, 75, 77, 82 Y 88


Mecanismos básicos / Basic switches




Interrupor unipolar / Single-pole switch
XXXX101-XXX



Interrupor unipolar / Single-pole switch
7700101-039




Pulsador / Push button switch
XXXX150-XXX



Pulsador / Push button switch
7700150-039



Interrupor bipolar / Double pole switch
XXXX133-XXX



Conmutador / 2-way switch
XXXX201-XXX



Conmutador / 2-way switch
7700201-039



Conmutador cruce / Intermediate switch
XXXX251-XXX



Conmutador cruce / Intermediate switch
7700251-039



Grupo 2 interruptores / 2 switches group
XXXX398-XXX



Pulsador desconexión / Push button disconnection switch
XXXX152-XXX



Grupo dos conmutadores / 2-way switches group
XXXX397-XXX



Grupo de pulsadores desconexión / Push button switch
disconnection group XXXX395-XXX



Grupo conmutador y pulsador / 2-way and push button switch group
XXXX301-XXX



Interrupor unipolar / Single-pole switch
XXXX102-XXX




Interrupor con piloto / Push button pilot switch
7700112-039



Interrupor bipolar / Double pole switch
XXXX134-XXX



Conmutador / 2-way switch
XXXX202-XXX



Interruptor unipolar con luminoso / Single-pole switch with light
XXXX104-XXX



Pulsador con luminoso / Push button switch with light
XXXX160-XXX



Pulsador con luminoso / Push button switch with light
7700160-039



Conmutador con luminoso / 2-way switch with light
XXXX204-XXX



Conmutador cruce con luminoso / Intermediate switch with light
XXXX254-XXX