

Double-pole switch 16AX 250V~ with screw terminal connection system ivory Simon 27 Play

REF. 27133-62



BASIC INFORMATION

DESCRIPTION

two-pole switch of 16AX and 250V of voltage with screw terminal connection system in ivory colour and belonging to the Simon 27 Play series. Its type of operation is tilting and is a double-pole switch suitable for installation both in surface-mounted and recessed way. It has 2 modules and supports a cable section of 1.5 to 2.5 mm with a stripped 11 mm, it also, you can install perfectly in rooms with a temperature of between 5 and 40°C, although it is also perfectly, in places where the temperature is place between -25 to 75°C. This switch is made of metal components with halogen-free insulation and thermoset trim and its dimensions are 45x45mm. To clean this switch you just need a soft, dry cloth and forget you to use any abrasive cleaner or abrasive cloths containing chlorine. The Simon 27 Play range of products, formed by covers, frames and rockers with mechanisms, allows you to enjoy decorating, as it is a revolutionary concept that allows you to take the initiative in redecorating your own spaces.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 AX	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP21	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
INDICATOR FUNCTION No	TYPE OF MECHANISM Pivoting	VERSION Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 11	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal, American and Centralisations	INSTALLATION TYPE Suitable for surface and flush mounting
CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053251522

UNITARY PACKAGING HEIGHT

36.5

UNITARY PACKAGING WIDTH

45.7

UNITARY PACKAGING LENGTH

46.3

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.077

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.048

PRODUCT NET WEIGHT

0.039

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053036044

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

53

PACKAGING WIDTH

160

PACKAGING LENGTH

220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1.866

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.476

PACKAGING NET WEIGHT

0.39

PACKAGING WEIGHT UNIT

KGM

MECANISMOS SIMON 27, 28 Y 44

Mecanismos básicos / Basic switches



Interrupor unipolar / Single-pole switch
XX00101-XX



Pulsador / Push button switch
XX00150-XX



Interrupor bipolar / Double pole switch
XX00133-XX




Conmutador / 2-way switch
XX00201-XX



Conmutador cruce / Intermediate switch
XX00251-XX

Mecanismos con piloto / Pilot switches



Interrupor unipolar / Single-pole switch
XX00102-XX



Interrupor bipolar / Double pole switch
XX00134-XX



Conmutador / 2-way switch
XX00202-XX



Interrupor unipolar / Single-pole switch
XX00104-XX



Pulsador / Push button switch
XX00160-XX



Conmutador / 2-way switch
XX2700204-XX



Conmutador cruce / Intermediate switch
XX2700254-XX