

Spotlight 880.34 industrial 3000 K ASYM

REF. 88034038-273



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

115,3 lm/W

IK CLASSIFICATION

08

CRI

70

LUMENS (LM)

23050 lm

IP RATING

IP65

DIRECTIONAL

Yes

LUMENS/W

23050lm/ 200W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

DRIVER INCLUDED

Yes

OPTICS

Asymmetric

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

200 W

COLOR TYPE

WW

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface (with bracket)

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053205563

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

8.5

PRODUCT NET WEIGHT

6.5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053205563

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

560

PACKAGING LENGTH

465

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

35154000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

8.5

PACKAGING NET WEIGHT

6.5

PACKAGING WEIGHT UNIT

KGM